

**MATERIAL SAFETY DATA SHEET**  
**365 AND 450 INTERIOR FLAT LATEX WALL PAINT**

---

**SECTION I - PRODUCT IDENTIFICATION**

---

**NAME**..... Corlin Paint Company  
**ADDRESS**..... 46 Loren Ave.  
Chico, CA 95928  
**EMERGENCY TELEPHONE #**..... (530) 894-3386 or call your Local  
Poison Control Center (800) 876-4766  
**PRODUCT NAME**..... Interior Flat Latex  
**PRODUCT CLASS**..... Vinyl-Acrylic Latex  
**HIMS RATING**..... HEALTH 1  
FLAMMABILITY 0  
REACTIVITY 0  
PERSONAL PROTECTIVE EQUIPMENT B

---

**SECTION II - HAZARDOUS INGREDIENTS**

---

INGREDIENT	PERCENT	TLV	mg/M3
		PPM	
NUOSEPT @ CAS #56709-13-8	Less Than 0.1%		

**NOTE-** This product contains pigments such as mineral silicates, silicone dioxide and titanium dioxide, which are not hazardous in wet paint, but may reach hazardous levels in dusts generated from sanding or grinding of dried paint. The risk depending on the duration and level of exposure.

**WARNING-** In compliance with the State of California's Proposition 65, the following statement is included: This product may contain trace amounts of one or more chemicals known to the State of California as a cancer hazard and a reproductive hazard.

---

**SECTION III - PHYSICAL DATA**

---

**BOILING RANGE**..... APPROXIMATELY 212degrees  
**VAPOR DENSITY**..... LIGHTER THAN AIR  
**EVAPORATION RATE**..... SLOWER THAN ETHER  
**VOLATILE VOLUME**..... 66 - 70%  
**WEIGHT/GALLON**..... 11.4 - 11.8/gal

**MATERIAL SAFETY DATA SHEET**  
**365 AND 450 INTERIOR FLAT LATEX WALL PAINT**

---

**SECTION IV - FIRE AND EXPLOSIONS HAZARD**

---

**FLAMMABILITY CLASSIFICATION:** OSHA - N/A  
DOT - N/A

**FLASH POINT:** None

**EXTINGUISHING MEDIA:** Not Applicable

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may build up pressure or explode when exposed to extreme heat.

**SPECIAL FIRE FIGHTING PROCEDURES:** None

---

**SECTION V - HEALTH HAZARD DATA**

---

**EFFECTS OF OVER EXPOSURE:**

**INHALATION:** May cause headache or nausea.

**SKIN CONTACT:** Wash off with soap and water. Remove contaminated clothing. (material is slightly alkaline).

**EYE CONTACT:** Direct eye contact may cause eye irritation.

**INGESTION:** Consult physician immediately and treat symptomatically.

**MEDICAL CONDITIONS PRONE TO AGGRIVATION BY EXPOSURE:**

Existing respiratory problems may be aggravated by exposure.

---

**EMERGENCY AND FIRST AID PROCEDURES:**

**INHALATION:** No emergency care anticipated, expose to fresh air.

**EYE CONTACT:** Flush immediately with large amounts of water for at least 15 minutes. Consult physician for medical treatment.

**SKIN CONTACT:** Wash off with soap and water. Remove contaminated clothing.

**INGESTION:** Drink one or two glasses of water. DO NOT induce vomiting. Consult physician immediately.

**MATERIAL SAFETY DATA SHEET**  
**365 AND 450 INTERIOR FLAT LATEX WALL PAINT**

---

**SECTION VI - REACTIVITY DATA**

---

**STABILITY:** Stable.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**HAZARDOUS DECOMPOSITION PRODUCTS:** May produce fumes when heated to decomposition as in burning. Fumes may contain carbon dioxide & monoxide.

**INCOMPATIBILITY--MATERIALS TO AVOID:** Unknown.

---

**SECTION VII - SPILL OR LEAK PROCEDURES**

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

Soak up and remove with absorbent inert material. Provide adequate ventilation.

**WASTE DISPOSAL METHOD:** Dispose in accordance with local, state and federal regulations. Do not incinerate closed containers.

---

**SECTION VIII - SAFE HANDLING AND USE INFORMATION**

---

**RESPIRATORY PROTECTION:** Use respirator or particle mask to avoid breathing spray mist.

**VENTILATION:** Provide sufficient ventilation, in volume and pattern to keep TLV below acceptable OSHA limit.

**EYE PROTECTION:** Goggles or safety glasses with side shields.

---

**SECTION IX - SPECIAL PRECAUTIONS**

---

**PRECAUTIONS TO BE TAKEN IN HANDLING & STORING:** Keep from freezing. Keep containers upright and tightly closed to prevent leakage.

**OTHER PRECAUTIONS:** Do not ingest. Keep out of reach of children.

This information is furnished without warranty, except it is accurate to the best of Corlin Paints' knowledge or obtained from sources believed to be accurate. This information is not to be construed as representation for which Corlin Paint assumes legal responsibility expressed or implied.