



PRODUCT PROFILE

450 PREMIUM INTERIOR FLAT LATEX

1950 Dr. Martin Luther King Jr. Pkwy. - Chico, Ca 95928 - (530) 345-9595 - Fax (530) 345-3589

DESCRIPTION:

450 premium latex is a superior quality vinyl acrylic flat latex paint. 450 provides maximum hiding with the features of excellent touch-up and washability. Use on all interior drywall, plaster, wood, or concrete walls and ceilings where a satin finish is desired.

PHYSICAL PROPERTIES	
COLOR	WHITE AND BASES
FINISH	FLAT
SOLVENT	WATER
DRY TO TOUCH	1-2 HOURS
% SOLIDS BY VOLUME	31%
% SOLIDS BY WEIGHT	50%
COVERAGE	300-400 SQUARE FEET
VISCOSITY	93-98 KREB UNITS
RECOAT TIME	2-4 HOURS

V.O.C.: LESS THAN 100 GRAMS PER LITER

ADVANTAGES:

- * Fast drying
- * Excellent hiding
- * Meets clean air standards
- * Superb touch-up
- * Water thinned
- * Extremely durable
- * Easy application
- * Outstanding adhesion

**Refer to label for cautions and warnings



PRODUCT PROFILE

450 PREMIUM INTERIOR FLAT LATEX

1950 Dr. Martin Luther King Jr. Pkwy. - Chico, Ca 95928 - (530) 345-9595 - Fax (530) 345-3589

TYPE OF PRODUCT:

A premium quality vinyl-acrylic latex wall paint, easy to apply, with maximum hiding, featuring excellent touch-up and washability.

TYPICAL USES:

All interior drywall, plaster, concrete or hardboard surfaces where a flat finish is desired.

SURFACE PREPARATION:

Be sure all surfaces are dry, free from dirt, grease, wax, chalky paint, rust, efflorescence and stains. Dull or etch glossy, glazed or dense surfaces. Neutralize alkali conditions, remove and kill all mildew or any other contamination that would adversely affect the performance of this coating.

APPLICATION:

May be applied by brush, roller or airless spray equipment. If brushing, a good quality nylon brush is recommended. Do not apply when material, air and/or surface temperature below 50°F.

DRYING TIME:

1-2 hours under normal conditions, a second coat may be applied in 2-4 hours depending on conditions.

PREVIOUSLY PAINTED SURFACES:

Fill or patch holes, spot prime bare or patched areas, or prime entire surface. Apply one or more coats as required.

NEW SURFACES:

Two coats are recommended for maximum washability. May be applied directly to new wood, drywall, concrete and plaster.

COVERAGE:

Approx. 300-400 square feet per gallon, depending on texture porosity of the surface to be painted.

THINNING AND CLEAN-UP:

Formulated ready for use. If thinning is necessary use small amount of water. Do not over thin. Clean brushes and equipment with water immediately after use.

COLORS:

White and Tint Bases

PACKAGE SIZES: 5 gallon, 1 gallon, quarts

APPROX. WEIGHT PER GAL: 11.8 LB.