



PRODUCT PROFILE
51 EXTERIOR FLAT LATEX
100% ACRYLIC

1950 Dr. Martin Luther King Jr. Pkwy. - Chico, Ca 95928 - (530) 345-9595 - Fax (530) 345-3589

DESCRIPTION:

51 Exterior flat latex is a fast drying 100% acrylic paint for new or old wood and masonry surfaces. 51 is an extremely durable exterior flat acrylic finish. It features excellent adhesion and superior color retention.

PHYSICAL PROPERTIES	
COLOR	WHITE, 6 STOCK COLORS, BASES
FINISH	FLAT
SOLVENT	WATER
DRY TO TOUCH	2 HOURS
% SOLIDS BY VOLUME	39%
% SOLIDS BY WEIGHT	56%
COVERAGE	250-350 SMOOTH 150-250 ROUGH
VISCOSITY	93-98 KREB UNITS
RECOAT TIME	6-12 HOURS

V.O.C.: LESS THAN 100 GRAMS PER LITER

ADVANTAGES:

- * Fast drying
- * Superior color retention
- * Meets clean air standards
- * One coat finish
- * Water thinned
- * Extremely durable
- * Easy application
- * Outstanding adhesion

**Refer to label for cautions and warnings



PRODUCT PROFILE

51 EXTERIOR FLAT LATEX

100% ACRYLIC

1950 Dr. Martin Luther King Jr. Pkwy. - Chico, Ca 95928 - (530) 345-9595 - Fax (530) 345-3589

TYPE OF PRODUCT:

An extremely durable exterior flat acrylic finish. It features excellent adhesion and superior color retention.

TYPICAL USES:

Wood, stucco, masonry, may be used for new or previously painted surfaces. New or old wood, shake or shingles, rough or smooth siding. Also, concrete, masonry, stucco, and properly primed metal surfaces.

SURFACE PREPARATION:

Be sure all surfaces are dry, free from dirt, grease, wax, chalky paint, rust, efflorescence and stains. Dull or etch glossy, glazed or dense surfaces. Neutralize alkali conditions, remove and kill all mildew or any other contamination that would adversely affect the performance of this coating.

APPLICATION:

May be applied by brush, roller or airless spray equipment. Do not apply in temperature below 50°F.

DRYING TIME:

2-4 hours under normal conditions, more time is required during cool, damp weather. Recoat in 6-12 hours.

PREVIOUSLY PAINTED SURFACES:

Scrape or use a water blaster to remove all loose peeling paint. Patch and prime with either Corlin 068 Latex Primer or use 51 as a primer. Apply one or more coats as required.

NEW SURFACES:

Prime new redwood and cedar with Corlin Exterior Primer 068 or an oil base primer. 51 may be applied to new wood, stucco, masonry.

COVERAGE:

250-350 square feet per gallon over smooth sealed surfaces. 150-250 square feet per gallon rough unsealed surfaces.

THINNING AND CLEAN-UP:

Formulated ready for use. If thinning is necessary use small amount of water. Do not over thin. Clean brushes and equipment with water immediately after use.

COLORS:

White and Tint Bases, 6 pre-mixed colors

PACKAGE SIZES: 5 gallon, 1 gallon, quarts

APPROX. WEIGHT PER GAL: 11.8 LB.